

Breaking the rules. TE 3000-AVR Breaker



Order Information

Description	Package Contents	Item No.
TE 3000-AVR Performance Package Deluxe	Includes tool, Tool cart, (1) TE-H28 SM 40 Pointed Chisel and (1) TE-H28 FM 40 Flat Self-Sharpening Chisel	03468966
TE 3000-AVR Performance Package	Includes tool, (1) TE-H28 SM 40 Pointed Chisel and (1) TE-H28 FM 40 Flat Self-Sharpening Chisel	03468967
TE 3000-AVR Cart	Tool cart for easy transport of the TE 3000-AVR	00401293

Technical Data	TE 3000-AVR
Power input	1800 W
Voltage	120 V
Hammering frequency	840 bpm
Single impact energy	50 ft-lbs
Weight	66 lbs
Dimensions (L x W x H)	32 x 24 x 8 in

Applications

- Medium- to heavy-duty demolition of concrete slabs and foundations
- Concrete removal for rebar connections and utility connections
- Tamping earthwork and digging in clay
- Penetrations for pipes, electrical boxes, HVAC, beams, etc.
- Asphalt and road patchwork

Outperform

- Over 50 foot-pounds of impact energy results in outstanding demolition performance and productivity
- SR brushless motor delivers tremendous demolition performance while keeping weight down
- Active Vibration Reduction achieves the lowest vibration in its class
- TE-H Polygon Self-Sharpening Chisels provide strong breaking power and stick less in concrete

Outlast

- New brushless SR motor eliminates need to replace carbon brushes and provides longer intervals between service
- Active Cooling System for the motor, electronics, and hammering mechanism keeps the tool and its casing cool for added durability
- Three-chamber sealing principle means longer lasting life with less breakdowns
- Power Conditioning System protects the motor against power surges and drains
- Supported by Hilti Lifetime Service which includes the 2 year No-Cost coverage

Hilti. Outperform. Outlast.